

CORSO

Corso is a porcelain interpretation of travertine with a subtly rustic appeal. The graphic includes the characteristic movement of travertine, including charming imperfections and small areas of fill. It has a slightly

chiseled edge but it's a rectified material, so customers can get different aesthetic results based on what grout joint size they prefer. It comes in two warm colors that are trending and are perfectly appropriate for a travertine look.



Avorio Natural (VWCOAON)



Beige Natural (VWCOBEN)

Product Information

Colors



VWCOAON Avorio Natural



VWCOBEN Beige Natural

Colors are intended as a guide only and may vary from actual tile. Sizes listed are nominal. Please check samples before making final selection and to get actual dimensions for layout.

Size (Rectified)

12 x 24 Natural VWCO--N/1224

Trim

The surface bullnose is made from field tile that is cut, ground and re-glazed.

VWCO--N/SBN 3 x 24 Surface Bullnose

Usage & Installation Information

Corso is suitable for residential to light and moderate commercial applications. To attain the proper mix of graphics and color it is important to pull from multiple boxes during installation, rotate pieces, and note the placement of the different images to get the proper final blend.

Most Italian manufacturers recommend a maximum offset of 8" (20cm) on all large format tiles when setting a running bond. Please refer to ANSI requirements for setting large format tiles (ANSI A 108.2 Section 4.3.8). There are special setting requirements and materials for large format tiles. Please refer to the TCNA Handbook and guidelines by your mortar manufacturer for more information.



Technical Information (Natural Finish)

Physical Properties	Norms	Value
Water Absorption	10545-3	<0.5%
Frost Resistance	10545-12	Resistant
Slip Resistance	DIN51130	R10 B
Dynamic Coefficient of Friction	ANSI A 137.1 BOT3000	Wet \geq 0.42

The Dynamic Coefficient of Friction is a general guide only. Testing may vary with different production runs and with different testing labs. As noted in the American with Disabilities Act (ADA) the coefficient of friction varies considerably due to facts not under the control of entities such as the manufacturers and distributors. These factors include, but are not limited to, contaminants, slope of terrain, drainage conditions, adjacent surfaces, etc. Suitability for any installation can only be determined by a site examination of all conditions that could affect the slip resistance of the tile being installed. Continual cleaning and maintenance must be performed once the tile has been installed.