

ARGENTA

Etienne



Etienne is a rectified porcelain with an authentic French limestone look. The graphic variation includes a mix of different limestone finishes - aged and waxed - including some pieces that have oxidation marks caused by exposure to sun and rain. It should be noted that there is quite a bit of graphic variation in this line, including a significant percentage of pieces that have the characteristic fossils of the stone. It is important to blend the material well during installation, pulling from multiple cartons and laying out the pieces carefully to get the right blend. The final look is impactful and, at its competitive price point, this series is a true value.



White (AAEEWE)



Ivory (AAEEIY)



Greige (AAEEGE)



Nut (AAEENT)

Colors are intended as a guide only and may vary from actual tile. Sizes listed are nominal. Please check samples before making final selection and to get actual dimensions for layout. See reverse side for additional product information.

Product Information

Colors

Greige	AAEEGE
Ivory	AAEEIY
Nut	AAEENT
White	AAEEWE

Size (Rectified)

12 x 24	AAEE--/1224
24 x 48*	AAEE--/2448

*The 24 x 48 is stocked in Ivory (IY) & White (WE) colors.

Due to the special packing required for the large format tiles, orders for the 24 x 48 size must be for full box quantities only & we are not able to fill orders on the same day as placed.

Trim

The surface bullnose is made from field tile that is cut, ground and reglazed.

3 x 24 Surface Bullnose AAEE--/SBN

Usage

Etienne is suitable for residential and moderate commercial applications.

Installation

Most tile manufacturers recommend a maximum offset of 8" (20 cm) on all large format tiles when setting a running bond. Please refer to ANSI requirements for setting large format tiles, ANSI A 108.2 section 4.3.8. Using a leveling system can improve the installation of this product.

To attain the proper mix of graphics and color it is important to pull from multiple boxes during installation, rotate pieces, and note the placement of the different images to get the proper final blend.

Technical Information

Physical Properties	Norms	Value
Flexion Resistance	10545-04	R ≥ 35 N/mm ² (average value)
Water Absorption	10545-03	≤ 0,05
Frost Resistance	10545-12	Resistant
Slip Resistance	DIN 51130	R10 B
PEI	10545-7	4
**Dynamic (DCOF) Coefficient of Friction	ANSI A137.1	Wet ≥ 0.42

** These results are for the natural finish and for the normal productions; if there is concern about a particular production, it should be tested. The Coefficient of Friction is a general guide only. Testing may vary with different production runs and with different testing labs.

As noted in the Americans with Disabilities Act (ADA) the coefficient of friction varies considerably due to facts not under the control of entities such as the manufacturers and distributors. These factors include, but are not limited to, contaminants, slope of terrain, drainage conditions, adjacent surfaces, etc. Suitability for any installation can only be determined by a site examination of all conditions that could affect the slip resistance of the tile being installed. Continual cleaning and maintenance must be performed once the tile has been installed.

Mosaic Available in all colors

Brick Mosaic AAEE--/BK



Brick Mosaic: 1-1/2 x 3 pieces laid out in a brick pattern.

Non-Stock Sizes (Rectified)

For projects that meet minimum quantities

Available in all colors

24 x 24 AAEE--/2424

Available in Greige (GE) & Nut (NT)

24 x 48* AAEE--/2448

*The other two colors (IY) & (WE) are stocked colors.