



Koru is an interpretation of the wood found in fruit trees, characterized by light veining and distinctive knots. The name Koru derives from a Maori word and symbol representing new life, growth and peace. The colors of Mirage's Koru are clean and crisp, creating a final look that creates a peaceful living space. The classic, natural colors are further enhanced by the opaque surface that absorbs light rather than reflecting it. The innovative finish and the high number of different images make this wood look porcelain incredibly realistic and universally appealing.



Apple (MEKO01)



Peach (MEKO02)



Apricot (MEKO03)



Nut (MEKO04)

Colors are intended as a guide only and may vary from actual tile. Sizes listed are nominal. Please check samples before making final selection and to get actual dimensions for layout. See reverse side for additional product information.

PRODUCT INFORMATION

Size - Rectified

8 x 48 MEKO--/848

Colors

- MEKO01 Apple (White/Ivory)
- MEKO02 Peach (Greige)
- MEKO03 Apricot (Beige/Honey)
- MEKO04 Nut (Walnut)





INSTALLATION INFORMATION

We recommend using a tile leveling system to install this product

Before installing the tile you should:

- Ensure the perfect planarity (flatness) of underlying floor base.
- Always double-check the quality of the tiles.
- When setting, tile should be only slightly staggered so that the ends of the tiles are within 8" or less from the ends of the corresponding staggered tile. (See figures 1 & 2)
- Staggered spacing does not need to be uniform, but should not exceed 8" recommendation.
- It is preferable to use a grouting material that matches the color of the tiles.

As with all inkjet lines, there are many different graphics that are mixed and packed randomly. It is important to pull from multiple boxes during installation, rotate pieces and note the placement of the different images in order to get the proper final blend. Koru is suitable for both residential and commercial settings with medium to high foot traffic.



Technical Information



Frost Resistance	Water Absorption	Slip Resistance	Coefficient of Friction	Dynamic & Static Coefficient of Friction
No Damage	≤ 0,05	R9	WET: ≥0,60 DRY: ≥0,60	≥0,42

The Coefficient of Friction is a general guide only. Testing may vary with different production runs and with different testing labs. As noted in the American with Disabilities Act (ADA) the coefficient of friction varies considerably due to facts not under the control of entities such as the manufacturers and distributors. These factors include, but are not limited to, contaminants, slope of terrain, drainage conditions, adjacent surfaces, etc. Suitability for any installation can only be determined by a site examination of all conditions that could affect the slip resistance of the tile being installed. Continual cleaning and maintenance must be performed once the tile has been installed. For more information see our current handout *Americans with Disabilities Act and Slip Resistance of Tile*.