



Marca Corona is expanding their impressive collection of marble looks with three stunning new marbles in the Foyer Royal series. The Cozy color is a warm, creamy sandstone look (the Turkish Marmo Mediterraneo), Delicate is a classic white marble (Italian Crema Delicato) and Chic is a soft grey (the French Gris de Savoie) that is perfectly on-trend.

All colors come in both Natural and Polished in 12 x 24 and a Herringbone mosaic in Natural. The Cozy also comes in additional sizes, the 24 x 48 in both finishes and the 4" Hexagon in Natural. To attain the proper mix of graphics, it is important to pull from multiple boxes during installation, rotate pieces and note the placement of the different images in order to get the proper final blend.



Delicate (MCFRDE)



Cozy (MCFRCY)



Chic (MCFRCC)

Colors are intended as a guide only and may vary from actual tile. Sizes listed are nominal. Please check samples before making final selection and to get actual dimensions for layout. See reverse side for additional product information.

Product Information

Colors


MCFRCC	Chic (Soft Grey)
MCFRCY	Cozy (Warm Cream)
MCFRDE	Delicate (Classic White)

Sizes (Rectified)	Natural Finish	Polished Finish
12 x 24	MCFR--N/1224	MCFR--P/1224
24 x 48* Cozy	MCFR--N/2448**	MCFR--P/2448


** The 24 x 48 Natural has a larger caliber and is not modular with the other sizes.

Mosaics (Natural Finish Only)

Herringbone	MCFR--N/HB	*The 24x48 size and the 4"
4" Hex* Cozy	MCFRCYN/4HX	Hex Natural is only available in Cozy (CY) color.



4" Hex Mosaic Natural (available in Cozy (CY) color only)



Herringbone Mosaic Natural (Available in all colors)

Due to the special packing required for the large format tiles, orders for the 24x48 size must be for full box quantities only & we are not able to fill orders on the same day as placed.

Trim	Natural Finish	Polished Finish
4 x 24 Surface Bullnose	MCFR--N/SBN	MCFR--P/SBN

The surface bullnose is made from field tile that is cut, ground and glazed.

Usage

Foyer Royal in Natural finish is suitable for residential and commercial applications.

For the Polished finish, please see notes below.

Installation Information

Most Italian manufacturers recommend a maximum offset of 8" (20cm) on all large format tiles when setting a running bond. Please refer to ANSI requirements for setting large format tiles, ANSI A 108.2 Section 4.3.8. There are special setting requirements and materials for large format tiles. Please refer to the TCNA Handbook and guidelines by your mortar manufacturer for more information. Using a leveling system can improve the installation of this product.

Polished Finish

The Polished finish is suitable for walls and for residential and light commercial floors that do not require DCOF. As with all shiny material, the polished surface is susceptible to scratching during installation and use, and extra care should be taken when handling the material. The factory does not recommend using an epoxy based grout because it can be very hard to remove from the surface of the tile during grouting. They also do not recommend using a sealer on the polished tiles.

Polished material can be etched with acids. Avoid detergents, solvents or acid-based products containing hydrochloric acid, citric acid, acetic acid or abrasive components. Do not use cleaning agents like abrasive cleaners which might scratch the surface. It is advisable to test a small area in a not highly visible section of the tiles before proceeding to clean the whole surface.

Physical Properties

Physical Properties	Norms	Value Natural	Physical Properties	Norms	Value Natural
Average Bending Strength	10545-04	45,5 N/mm ² (average value)	Frost Resistance	10545-12	Resistant
Breaking Strength	10545-04	S ≥ 1300 N	Slip Resistance	DIN 51130 DIN 51097	R9 ^o
Water Absorption	10545-03	≤ 0,05	** Dynamic (DCOF) Coefficient of Friction	BOT 3000 ANSI A 137.1	Wet ≥ 0.42



** These results are for the natural finish and for the normal productions; if there is concern about a particular production, it should be tested. The Coefficient of Friction is a general guide only. Testing may vary with different production runs and with different testing labs.

As noted in the Americans with Disabilities Act (ADA) the Dynamic Coefficient of friction varies considerably due to facts not under the control of entities such as the manufacturers and distributors. These factors include, but are not limited to, contaminants, slope of terrain, drainage conditions, adjacent surfaces, etc. Suitability for any installation can only be determined by a site examination of all conditions that could affect the slip resistance of the tile being installed. Continual cleaning and maintenance must be performed once the tile has been installed.