

# TERRAE<sub>by Euro</sub>

Terrae is a slate look that is modern and refined without sacrificing the recognizable and distinct appearance of slate. The earthy colors have the variation and movement of slate without being extreme.



Colors are intended as a guide only and may vary from actual tile. Sizes listed are nominal. Please check samples before making final selection and to get actual dimensions for layout. See reverse side for additional product information.

EOTE



White (EOTEWE)



Beige (EOTEBE)



Grey (EOTEGY)

## Product Information

### Colors

EOTEBE	Beige
EOTEGY	Grey
EOTEWE	White

### Size (Rectified)

12 x 24	EOTE--/1224
---------	-------------

### Mosaic

2 x 2	EOTE--/22
-------	-----------



2 x 2 mosaic -  
full sheet shown

### Trim

2-1/2 x 24 Surface Bullnose	EOTE--/SBN
-----------------------------	------------

### Usage & Handling

Terrae is suitable for residential and light commercial use.

### Installation

There are many different graphics that are mixed and packed randomly. It is important to pull from multiple boxes during installation, rotate pieces and note the placement of the different images in order to get the proper final blend.

Most Italian manufacturers recommend a maximum offset of 8" (20cm) on all large format tiles when setting a running bond. Please refer to ANSI requirements for setting large format tiles (ANSI A 108.2 Section 4.3.8). There are special setting requirements and materials for large format tiles. Please refer to the TCNA Handbook and guidelines by your mortar manufacturer for more information.



## Technical Information

Physical Properties	Norms	Value
Deep Abrasion Resistance	10545-6	<150 mm <sup>3</sup> Conforms
PEI	10545-7	White - 5 Beige - 4 Grey - 3
Water Absorption	10545-3	Conforms
Frost Resistance	10545-12	Resistant
Breaking Strength	10545-4	Conforms
Slip Resistance	DIN51130	R10
Dynamic Coefficient of Friction (DCOF)	BOT 3000 STANDARD ANSI A326.3:2019	≥ 0.42 Wet

The Dynamic Coefficient of Friction is a general guide only. Testing may vary with different production runs and with different testing labs. As noted in the American with Disabilities Act (ADA) the coefficient of friction varies considerably due to facts not under the control of entities such as the manufacturers and distributors. These factors include, but are not limited to, contaminants, slope of terrain, drainage conditions, adjacent surfaces, etc. Suitability for any installation can only be determined by a site examination of all conditions that could affect the slip resistance of the tile being installed. Continual cleaning and maintenance must be performed once the tile has been installed. For more information see our current handout *Americans with Disabilities Act and Slip Resistance of Tile*.