

TIMELESS

MADE IN ITALY



The features of this collection are reflected in its name. Timeless: beautiful tiles that go beyond time and trends. From the aesthetic point of view, the color palette stands out for its neutral colors and subtle movement, allowing for harmonious combinations. From the technical point of view, Casalgrande has fine-tuned their technology for making full-body porcelain, and they manufacture a material with superior technical characteristics that withstand the test of time. This is a truly unglazed, technical porcelain, with all the graphic movement achieved by the pigments in the clay and no glaze on top.



Thunder (CETSTR)

G1



Ice (CETSIE)

G2



Seal (CETSSL)

G1



Charcoal (CETSCL)

G1



Taupe (CETSTE)

G1

G1 - Group 1 Pricing

G2 - Group 2 Pricing

Colors are intended as a guide only and may vary from actual tile. Sizes listed are nominal. Please check samples before making final selection and to get actual dimensions for layout. See reverse side for additional product information.

Product Information

Colors

Group 1	Group 2
CETSCL Charcoal	CETSIE Ice (White)
CETSSL Seal (Medium Grey)	
CETSTE Taupe	
CETSTR Thunder (Light Greige)	

Sizes (Rectified)

12 x 24	CETS--/1224
24 x 48*	CETS--/2448

*Due to the special packing required for the large format tiles, orders for the 24x48 size must be for full box quantities only & we are not able to fill orders on the same day as placed.

Mosaic

2 x 2	CETS--/22
-------	-----------

Trim

3-1/2 x 24 Surface Bullnose	CETS--/SBN
-----------------------------	------------

Installation

To attain the proper mix of graphics and color it is important to pull from multiple boxes during installation, rotate pieces, and note the placement of the different images to get the proper final blend. Most Italian manufacturer recommend a maximum offset of 8" (20 cm) on all large format tiles when setting a running bond. Please refer to ANSI requirements for setting large format tiles, ANSI A 108.2 section 4.3.8. Using a leveling system can improve the installation of this product.



Usage & Handling

Timeless is suitable for residential and commercial use.

TECHNICAL INFORMATION

Physical Properties	Norms	Value
Deep Abrasion Resistance	10545-6	<150 mm ³ Conforms
PEI	N/A	See 'Deep Abrasion'
Water Absorption	10545-3	Conforms
Frost Resistance	10545-12	Resistant
Breaking Strength	10545-4	Conforms
Slip Resistance	DIN51130	R9
Dynamic Coefficient of Friction (DCOF)	BOT 3000 STANDARD ANSI A326.3:2021	≥ 0.42 Wet

The Dynamic Coefficient of Friction is a general guide only. Testing may vary with different production runs and with different testing labs. As noted in the American with Disabilities Act (ADA) the coefficient of friction varies considerably due to facts not under the control of entities such as the manufacturers and distributors. These factors include, but are not limited to, contaminants, slope of terrain, drainage conditions, adjacent surfaces, etc. Suitability for any installation can only be determined by a site examination of all conditions that could affect the slip resistance of the tile being installed. Continual cleaning and maintenance must be performed once the tile has been installed. For more information see our current handout *Americans with Disabilities Act and Slip Resistance of Tile*.