



The Tex series blends concrete with textures that recall natural fabrics, creating a subtle textile look. The richness of the line comes from the color palette; each color includes multiple tones that give it depth and complexity. This series is modern yet warm and inviting.



Juta (PSTXJA)



Khadi (PSTXKI)



Shantung (PSTXSG)



Satin (PSTXSN)



Velvet (PSTXVT)

Colors are intended as a guide only and may vary from actual tile. Sizes listed are nominal. Please check samples before making final selection and to get actual dimensions for layout. See reverse side for additional product information.

Colors

Juta (Brown/Taupe)	PSTXJA
Khadi (Beige)	PSTXKI
Satin (Greige)	PSTXSN
Shantung (White)	PSTXSG
Velvet (Charcoal)	PSTXVT

The Double Weave Mosaic is perfect for accents, feature walls and large areas. It is also a practical alternative to using 2x2 on shower pans and adds an upgraded aesthetic to this important function.



Double Weave Mosaic
PSTX--/DW

Size (Rectified)

12 x 24 PSTX--/1224

It can be cut into strips to make a striking decorative accent.

Mosaic

Double Weave Mosaic PSTX--/DW

Trim

The surface bullnose is made from field tile that is cut, ground and reglazed.
3 x 24 Surface Bullnose PSTX--/SBN

Usage

Tex is suitable for residential and light to moderate commercial applications.

Installation

It is important to blend tile within each carton and from multiple cartons during installation, as well as changing the orientation of pieces with similar graphics to attain a proper mix.

Most Italian manufacturers recommend a maximum offset of 8" (20 cm) on all large format tiles when setting a running bond. Please refer to ANSI requirements for setting large format tiles, ANSI A 108.2 section 4.3.8. Using a leveling system can improve the installation of this product.

Non-stock sizes (Rectified)

For projects that meet minimum quantities
Available in all colors

24 x 24	PSTX--/2424
24 x 48	PSTX--/2448
36 x 36	PSTX--/3636

Physical Properties

Physical Properties	Norms	Value
Bending Strength	10545-04	R ≥ 35 N/mm ² (average value)
Water Absorption	10545-03	≤ 0,05
Frost Resistance	10545-12	Resistant
Slip Resistance	DIN 51130 DIN 51097	R10 A
** Dynamic (DCOF) Coefficient of Friction	ANSI A 137.1 BOT 3000E	Wet ≥ 0.42



** These results are for the natural finish and for the normal productions; if there is concern about a particular production, it should be tested. The Dynamic Coefficient of Friction is a general guide only. Testing may vary with different production runs and with different testing labs.

As noted in the Americans with Disabilities Act (ADA) the dynamic coefficient of friction varies considerably due to facts not under the control of entities such as the manufacturers and distributors. These factors include, but are not limited to, contaminants, slope of terrain, drainage conditions, adjacent surfaces, etc. Suitability for any installation can only be determined by a site examination of all conditions that could affect the slip resistance of the tile being installed. Continual cleaning and maintenance must be performed once the tile has been installed.