

VIEW

BAAR

Baar presents a realistic and elevated porcelain version of Jura stone. The graphic faithfully represents the real Jura, including the fossils that are characteristic of this distinctive limestone. Various prehistoric animals are evident, such as nautilus, annelids, and other interesting critters. The fossils are different sizes and shapes, with some light and some dark; they add depth and create beautiful

graphic movement. The three colors have gentle shade variation and a surface texture which add richness to the final look. As a stone look, this is a very sleek and sophisticated product.



Pure (VWBRPE)



Grey (VWBRGY)



Beige (VWBRBE)

Installation images above show non-stock sizes. Colors are intended as a guide only and may vary from actual tile. Sizes listed are nominal. Please check samples before making final selection and to get actual dimensions for layout. See reverse side for additional product information.

Product Information

Size (Rectified, Natural Finish)

12 x 24 VWBR--N/1224

Mosaic (Natural Finish)

2 x 2 VWBR--N/22

Trim (Natural Finish)

VWBR--N/SBN 3 x 24 Surface Bullnose

Made from field tile that is cut, ground and reglazed.

Colors



Beige (VWBRBE)



Grey (VWBRGY)



Pure (VWBRPE)

TECHNICAL INFORMATION

Physical Properties	Norms	Values
Abrasion Resistance - PEI	10545-7	PEI 5 Pure PEI 4 Beige & Grey
Water Absorption	10545-3	Conforms
Frost Resistance	10545-12	Resistant
Breaking Strength	10545-4	Conforms
Slip Resistance	DIN51130	R10 B
Dynamic Coefficient of Friction (DCOF)	BOT 3000 STANDARD ANSI A137.1	Wet \geq 0.42

The Dynamic Coefficient of Friction is a general guide only. Testing may vary with different production runs and with different testing labs. As noted in the American with Disabilities Act (ADA) the coefficient of friction varies considerably due to factors not under the control of entities such as the manufacturers and distributors. These factors include, but are not limited to, contaminants, slope of terrain, drainage conditions, adjacent surfaces, etc. Suitability for any installation can only be determined by a site examination of all conditions that could affect the slip resistance of the tile being installed. Continual cleaning and maintenance must be performed once the tile has been installed.

Usage and Installation Information

Baar is suitable for residential and light commercial applications. There are many different graphics that are mixed and packed randomly. It is important to pull from multiple boxes during installation, rotate pieces, and note the placement of the different images to get the proper final blend.

Most Italian manufacturers recommend a maximum offset of 8" (20cm) on all large format tiles when setting a running bond. Please refer to ANSI requirements for setting large format tiles (ANSI A 108.2 Section 4.3.8). There are special setting requirements and materials for large format tiles. Please refer to the TCNA Handbook and guidelines by your mortar manufacturer for more information.