

VIEW

MARAIS

Marais is a modern reinterpretation of Belgian Pierre Blue Stone. The black, Grafite, color is closest to the real bluestone and then View reimagined the look in three additional colors to create a four color line. The material has a slightly rustic edge, but it is still rectified and has a refined look. The 24x24 size is perfect for this look and helps the line stand out.



Beige (VWMSBEN)
Shown in 36 x 36 non-stock size



Argento (VWMSAON)



Avana (VWMSAAN)
Shown in 36 x 36 non-stock size



Grafite (VWMSGEN)

Installation images above show non-stock sizes. Colors are intended as a guide only and may vary from actual tile. Sizes listed are nominal. Please check samples before making final selection and to get actual dimensions for layout. See reverse side for additional product information.

Product Information

Size and Colors (Rectified, Natural Finish)



24 x 24 Avana (VWMSAAN/2424)



24 x 24 Argento (VWMSAON/2424)



24 x 24 Beige (VWMSBEN/2424)



24 x 24 Grafite (VWMSGEN/2424)

Mosaic (Natural Finish)

3 x 3 VWMS--N/33

Trim (Natural Finish) Made from field tile that is cut, ground and reglazed.

VWMS--N/SB 3 x 24 Surface Bullnose

Usage and Installation Information

Marais is suitable for residential and light commercial applications. There are many different graphics that are mixed and packed randomly. It is important to pull from multiple boxes during installation, rotate pieces, and note the placement of the different images to get the proper final blend.

Most Italian manufacturers recommend a maximum offset of 8" (20cm) on all large format tiles when setting a running bond. Please refer to ANSI requirements for setting large format tiles (ANSI A 108.2 Section 4.3.8). There are special setting requirements and materials for large format tiles. Please refer to the TCNA Handbook and guidelines by your mortar manufacturer for more information.

TECHNICAL INFORMATION

Physical Properties	Norms	Values	Physical Properties	Norms	Values
Abrasion Resistance	10545-6	<math><175\text{mm}^3</math> Conforms	Breaking Strength	10545-4	Conforms
Water Absorption	10545-3	Conforms	Slip Resistance	DIN51130	R10 B
Frost Resistance	10545-12	Resistant	Dynamic Coefficient of Friction (DCOF)	BOT 3000 STANDARD ANSI A137.1	Wet ≥ 0.42

The Dynamic Coefficient of Friction is a general guide only. Testing may vary with different production runs and with different testing labs. As noted in the American with Disabilities Act (ADA) the coefficient of friction varies considerably due to facts

not under the control of entities such as the manufacturers and distributors. These factors include, but are not limited to, contaminants, slope of terrain, drainage conditions, adjacent surfaces, etc. Suitability for any installation can only be determined by a site examination of all conditions that could affect the slip resistance of the tile being installed. Continual cleaning and maintenance must be performed once the tile has been installed.