

Scultorea Statuario Argentio


MCSA

from MARCA CORONA



Scultorea features the quintessential white marble look of Statuario Argentio. By combining Marca Corona's stellar historical success with making white marbles and their updated and enhanced technology, this is the new, improved generation for statuario-look porcelain. We are stocking 12x24 and 24x48 in both Natural and Polished. Then there is a 2x10 size in the new Velvet finish which is like a silky honed marble. The 8-1/2" Hex and the mosaics come in Natural only.

Sizes: Rectified Available in Natural and Polished finishes



12 x 24 (MCSASAN/1224)

Colors are intended as a guide only and may vary from actual tile. Sizes listed are nominal. Please check samples before making final selection and to get actual dimensions for layout. See reverse side for additional product information.




24 x 48 (MCSASAN/2448)

Non-Rectified



8-1/2" Hex
(MCSASAN/9HX)

Natural finish only



2 x 10 (MCSASAV/210)
Velvet finish only

Product Information

Color Statuario Argento (MCSASA)

Sizes (Rectified)	Natural Finish	Polished Finish
12 x 24 24 x 48*	MCSASAN/1224 MCSASAN/2448	MCSASAP/1224 MCSASAP/2448
Non-Rectified 8-1/2" Hex	MCSASAN/9HX	*Due to the special packing required for the large format tiles, orders for the 24x48 size must be for full box quantities only & we are not able to fill orders on the same day as placed.
Non-Rectified 2 x 10	MCSASAV/210	

Trim	Natural Finish	Polished Finish
4 x 24 Surface Bullnose	MCSASAN/SBN	MCSASAP/SBN

The surface bullnose is made from field tile that is cut, ground and glazed.

Coordinating Trim	Natural Finish	Polished Finish
1/2 x 12 Pencil Bullnose	MCSASAN/112SBN	MCSASAP/112SBN

Expect shade variation between field and trim.

Installation Information

To attain the proper mix of graphics and color, it is important to pull from multiple boxes during installation, rotate pieces, and note the placement of the different images to get the proper final blend. Most Italian manufacturers recommend a maximum offset of 8" (20cm) on all large format tiles when setting a running bond. Please refer to ANSI requirements for setting large format tiles, ANSI A 108.2 Section 4.3.8. There are special setting requirements and materials for large format tiles. Please refer to the TCNA Handbook and guidelines by your mortar manufacturer for more information. Using a leveling system can improve the installation of this product.

Usage

Scultorea in Natural finish is suitable for residential and commercial applications. For the Polished finish, please see notes below.

Polished Finish

The Polished finish is suitable for walls and for residential and light commercial floors that do not require DCOF. As with all shiny material, the polished surface is susceptible to scratching during installation and use, and extra care should be taken when handling the material. The factory does not recommend using an epoxy based grout because it can be very hard to remove from the surface of the tile during grouting. They also do not recommend using a sealer on the polished tiles.

Polished material can be etched with acids. Avoid detergents, solvents or acid-based products containing hydrochloric acid, citric acid, acetic acid or abrasive components. Do not use cleaning agents like abrasive cleaners which might scratch the surface. It is advisable to test a small area in a not highly visible section of the tiles before proceeding to clean the whole surface.

TECHNICAL INFORMATION - NATURAL FINISH


Physical Properties	Norms	Value	Physical Properties	Norms	Value
Deep Abrasion Resistance	10545-6	<150 mm ³ Conforms	Breaking Strength	10545-4	Conforms
PEI - See "Deep Abrasion Resistance"	ISO 10545-7	N/A	Slip Resistance	DIN EN 16165:2023 Annex A & B	R9 A
Water Absorption	10545-3	Conforms	Dynamic Coefficient of Friction (DCOF)**	BOT 3000E STANDARD ANSI A326.3:2022	≥ 0.42 Wet
Frost Resistance	10545-12	Resistant			

** These results are for the natural finish and for the normal productions; if there is concern about a particular production, it should be tested. The Dynamic Coefficient of Friction is a general guide only. Testing may vary with different production runs and with different testing labs.

Mosaics (Natural Finish Only)



2 x 2
(MCSASAN/22)



Herringbone
(MCSASAN/HB)



4" Hex*
(MCSASAN/4HX)



8-1/2" Hex